

DECLARATION OF PERFORMANCE

No. 008CPR2013-07-01

Snow stop with two pipes

1.	Product-type:	Snow stop pipe	Fast	ener		Latch	
2.	Unique	610010-610075	611210	-611475	6112	410-6112675	
	identification						
	code of the						
	product-type:						
3.	Intended use:	For tiled and corrugated sheets, rolled steel roof.					
4.	Name,	AS Toode,					
	registered	Tule11, 76505 Saue,					
	trade name or	Harju county, Estonia					
	registered						
	trade mark						
	and contact						
	address of the						
	manufacturer:						
5.	Not applicable						
6.	System or						
	systems of						
	assessment and						
	verification of	System 3.					
	constancy of						
	performance of						
	the construction						
	product:						
7.	Type-approval tests performed by VTT Expert Services OY (NB 0809) according to the method of					od of	
0	EVS-EN 516 8.1.						
8.	Not applicable						
9.	Declared perform	iance					
	Essential characteristics Performance technica						
Es		ssential characteristics		Pertor	rmance	technical	
		Snow stop pipe	1.25 mm			specification	
	Material:		1.23 11111		S 320 GD		
		Fastener, latch	2.5 mm	332			
	Coatin-	Zink 350 g/m2					
Coating		Polyester powder coating					
Snow stop pipe		Length (mm):	3000				
	dimensions:	Diameter (mm):	32				
		Fire performance		Clas	ss A1		



External fire performance	Meets the requirements of external fire	
	performance	
Fastener's resistance to static load:	5kN	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Place and date of issue: Saue 01.07.2013

Name, title: Aivo Rosenberg Mati Kitt

General Manager Board Member
AS Toode AS Toode

Signature: