

DECLARATION OF PERFORMANCE

No. 001CPR2013-07-01

Tiled profile

1.	Product:	Self-supporting sheet metal roof and wall elements – Tiled profile				
2.	Product code:	340111 - 341433				
3.	Application:	Roof elements				
4.	Manufacturer:	AS Toode Tule 11, 76505 Saue				
	Harjumaa, Estonia					
5.	Not applicable					
6.	The systems for evaluating and		System 4.			
	inspecting performance					
-	resistance:					
7.	Not applicable					
8.	Not applicable					
9.	Declared performance					
Main characteristics		stics	Required	Allowed tolerance	Harmonized technical specification	
Rea	action to external f		Broof (t1), Broof (t2),		EN 14782 : 2006	
			BROOF (t3) - (CWFT)			
Rea	action to fire		ester 25 µm/ PVDF		(EVS EN 14782:2007)	
			m: A1 (CWFT);			
			ester 27 μm/ PVDF			
			>25-35 µm: A2-s1,d0;			
			PUR 50μm/ PURAL MATT			
			50μm/ NOVA 50μm/			
			A MATT 50 μm: A2-			
		s2,d0	-			
			PVC 200 μm: C-s3,d0			
Water resistance			product is			
		-	rproof			
Load bearing capacity						
Covering width of the plate, in			1100	± 2 mm		
mm						
Length of plate, in mm:		n:		± 3 mm		
Pitch gap of regular plate, in		late, in	350	± 2 mm		
mm:						
Pitch gap of EXTRA plate, in		ate, in	400	± 2 mm		
mm:						
Profile height of regular plate:		-	40	± 2 mm		
Profile height of EXTRA plate:			45	± 2 mm		
Steel sheet tolerance			EN 10143, EN 508-1			
Raw material:			mm; 0.5 mm; 0.6 mm			
Coating:			GD+Z275; DX51D+Z2			
			e: Polyester 25-27 μm			
			(polyurethane) 50 μm			
		μm, NOV	A 50 μm, NOVA MAT			



2.side: 5-10 µm

10. The performance of products determined in clauses 1 and 2 is in accordance with the declared performance described in clause 9. This declaration of performance is issued on the sole responsibility of the manufacturer determined in clause 4.

Signed by the representatives of the manufacturer: Place and date of issue: Saue July 1, 2013

for.

Name, position:

Aivo Rosenberg

Mati Kitt

Director General

AS Toode

Board Member AS Toode

Signature: